



V110 FULLY RUGGED NOTEBOOK

- Enhanced Enterprise Security with optional Intel vPro, Windows Disk Encryption, TPM 2.0 and many more multi-factor authentication options
- 10th Generation Intel® Core™ i7 / i5 vPro™ Processor
- 11.6" LumiBond® 2.0 Display with Getac Sunlight Readable Technology and Capacitive Touchscreen
- LifeSupport™ battery swappable technology
- Optional Dual Mode Touchscreen (multi-touch and digitizer)



Office Dock



Specifications

Operating System

Windows 10 Pro

Mobile Computing Platform

Intel® Core™ i5-10210U Processor 1.6GHz
Max. 4.2GHz with Intel® Turbo Boost Technology
- 6MB Intel® Smart Cache

Platform Options:

Intel® Core™ i5-10310U vPro™ processor 1.7GHz
Max. 4.4GHz with Intel® Turbo Boost Technology
- 6MB Intel® Smart Cache

Intel® Core™ i7-10510U Processor 1.8GHz
Max. 4.9GHz with Intel® Turbo Boost Technology
- 8MB Intel® Smart Cache

Intel® Core™ i7-10610U vPro™ Processor 1.8GHz
Max. 4.9GHz with Intel® Turbo Boost Technology
- 8MB Intel® Smart Cache

VGA Controller

Intel® UHD Graphics

Display

11.6" IPS TFT LCD FHD (1920 x 1080)
Protection Film
800 nits LumiBond® display with Getac sunlight readable technology
Capacitive multi-touch screen

Storage & Memory

8GB DDR4
Optional: 16GB / 32GB / 64GB DDR4
256GB PCIe NVMe SSD
Optional: 512GB / 1TB SSD PCIe NVMe SSD

Keyboard

LED backlit membrane keyboard
Optional: Rubber Keyboard

Pointing Device

Touchscreen
- Capacitive multi-touch screen
- Optional: Dual mode touchscreen (multi-touch and digitizer)

Touchpad

- Glide touchpad with left-click and right-click buttons

Expansion Slot

Smart Card Reader x 1
Optional: 1D/2D Imager Barcode Readerⁱ
Optional: USB 3.2 Gen 2 Type-C x 1ⁱ

I/O Interface

FHD webcam x 1^{vi}
Headphone out/Mic-in Combo x 1
DC in Jack x 1
USB 3.2 Gen 1 Type-A x 1
USB 3.2 Gen 2 Type-A x 2
LAN (RJ45) x 1
HDMI x 1
Serial port (9-pin; D-sub) x 1
Docking Connector x 1
Optional: Windows Hello face-authentication camera (front-facing) x 1^{vii}
Optional: RF antenna pass-through for GPS, WLAN and WWAN
Optional: 8M pixels auto focus rear camera x 1

Communication Interface

10/100/1000 base-T Ethernet
Intel® Wi-Fi 6 , AX200 802.11ax
Bluetooth (v5.2)^{ix}
Optional: Dedicated GPS
Optional: 4G LTE mobile broadband

Security Feature

TPM 2.0
Kensington Lock
Optional: Intel® vPro™ Technology
Optional: HF RFD and contactless Smart Card reader^{xi}
Optional: Fingerprint reader

Power

AC Adapter (65W, 100-240VAC, 50/60Hz)
Li-Ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2
LifeSupport™ battery swappable technology

Dimension (W x D x H) & Weight

313 x 238 x 39mm (12.32" x 9.37" x 1.53")
2.1kg (4.63lbs)^{xv}

Rugged Feature

MIL-STD-810H certified
IP65 certified
MIL-STD-461G certified^{xv}
Vibration & 4 feet (1.2m) drop resistant^{xi}
e-Mark certified for vehicle usage
Optional: ANSI / UL 121201, CSA C22.2 NO. 213^{xv}
Optional: Salt fog certified

Environmental Specification

Temperature^{xv}:
- Operating: -29°C to 63°C / -20°F to 145°F
- Storage: -51°C to 71°C / -60°F to 160°F
Humidity:
- 95% RH, non-condensing

Pre-installed Software

Getac Utility
Getac Camera
Getac Geolocation
Getac Barcode Manager^{viii}
Optional: Absolute Persistence®

Accessories

Battery (11.1V, typical 2100mAh; min. 2040mAh)
AC Adapter (65W, 100-240VAC)
Capacitive Stylus

Optional:

Carry Bag
Battery (11.1V, typical 2100mAh; min. 2040mAh)
Multi-Bay Charger (Dual Bay)
Multi-Bay Charger (Eight-Bay)
AC Adapter (65W, 100-240VAC)
Office Dock AC Adapter (90W, 100-240VAC)
MIL-STD-461 Certified AC Adapter (90W, 115-230VAC)
Vehicle Adapter (120W, 11-32VDC)
Digitizer Pen
Capacitive Stylus
Protection Film
X Strap
Shoulder Strap (2-point)
Vehicle Dock
Office Dock
100W Type-C Adapter^x

Bumper-to-Bumper Warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

- i Smart Card reader, optional 1D/2D imager barcode reader and optional USB 3.2 Gen 2 Type-C are mutually exclusive. (USB 3.2 Gen 2 Type-C is mutually exclusive with rear camera)
- ii Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- iii 13.56MHz Contactless HF RFID / NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- iv Weight and dimensions vary from configurations and optional accessories.
- v MIL-STD-461G 90W AC adapter sold separately.
- vi Tested by an independent third-party test lab following MIL-STD-810H.
- vii FHD webcam and optional Windows Hello face-authentication camera (front-facing) are mutually exclusive options.
- viii Available when barcode reader option is selected.
- ix Available with limited configurations.
- x Do not support the configurations with Discrete Graphic Card.
- xi Drop test results vary from configurations and optional accessories.

V110

Fully Rugged Notebook



Docking Solutions

	Vehicle Dock	Office Dock
Serial Port	2	2
External VGA	1	1
Microphone	1	1
Audio Output	1	1
DC in Jack	1	1
USB	4	4
LAN	1	1
HDMI	1	1
RF Antenna Connector	3 (WWAN, WLAN, GPS)	--

Getac

GETAC TECHNOLOGY CORPORATION

5F, Building A, No. 209, Section 1, Nangang Rd.,
Nangang Dist., Taipei City, 11568, Taiwan, R.O.C.
Tel : +886 2 2785 7888
globalmarketing@getac.com | www.getac.com



Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
Information provided herewith is for reference only,
available specification shall be subjected to quotation by request. V01M05Y21WWW