



ANS

enterp

ZX70 FULLY RUGGED TABLET

- Qualcomm[®] Snapdragon™ 660, Octa-core Processor
- Verified as Android enterprise recommended
- 7" LumiBond[®] display with Getac sunlight readable technology and glove-enabled capacitive touchscreen
- 6ft drop, MIL-STD-810H and IP67 certified
- Optional barcode reader, RFID reader



SPECIFICATIONS

Operating System Android™ 10.0

Mobile Computing Platform

Qualcomm[®] Snapdragon™ 660, Octa-core 1.95GHz Max. 2.2GHz

VGA Controller Qualcomm[®] Adreno™ 512 GPU

Display 7" Wide Viewing Angle TFT LCD HD (1280 x . 720) Protection film LumiBond[®] display with Getac sunlight readable technology Capacitive multi-touch screen

Storage & Memory 4GB LPDDR4 64GB eMMC

Kevboard Power button 3 tablet programmable buttons

Pointing Device Touchscreen - Capacitive multi-touch screen

Expansion Slot Optional: 1D/2D imager barcode reader

I/O Interface 8M pixels webcam x 1 12M pixels autofocus rear camera x 1 DC in Jack x 1 USB 2.0 (Host) x 1 MicroUSB 2.0 (Client) x 1 MicroSD x 1 Docking connector (Pogo/JAE) x 1 Optional: SIM card slot x 1 (Micro-SIM, 3FF) ^{III} Optional: RF antenna pass-through for GPS and ŴWAN

Communication Interface

Wi-Fi 802.11ac Bluetooth (v5.0) Dedicated GPS Optional: 4G LTE mobile broadband "

Security Features

Optional: HF RFID/NFC combo reader ^{iv, v} Power AC adapter (25W, 100-240VAC, 50/60Hz) Li-ion battery (3.8V, typical 8480mAh; min. 8220mAh)

Dimension (W x D x H) & Weight 218 x 142 x 27mm (8.58" x 5.6" x 1.08") 762g (1.68lbs) vi

Rugged Features MIL-STD-810H certified

IP67 certified Vibration & 6ft (1.8m) drop resistant ^{vii} Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D)

Environmental Specifications

Temperature ^{viii}: - Operating: -21°C to 60°C / -6°F to 140°F - Storage: -40°C to 71°C / -40°F to 160°F

Humidity: - 95% RH, non-condensing

Pre-installed software Getac File Browser Getac Camera Getac Input Method Getac Driving Safety Utility (trial version) Getac deployXpress (trial version) Getac settings and Google applications (Search, Chrome, Gmail, Maps, YouTube, Play, Drive, YouTube music, Play movies, Duo and photos)

Optional software

Getac Driving Safety Utility Getac deployXpress Getac OEMConfig

Accessories

AC adapter (25W; 12V/2A, 100-240VAC; 50/60Hz) Capacitive stylus with tether Pen holder Wrist strap

Optional:

Carry bag AC adapter (25W; 12V/2A, 100-240VAC; 50/60Hz) Office dock AC adapter (60W, 110-240VAC) DC-DC vehicle adapter (120W, 11-32VDC) Capacitive stylus with tether Protection film Shoulder strap (2-point) Wrist strap Rotating hand strap with kickstand and stylus holder Vehicle cradle ^{ix} USB to RS232 converter cable Docking connector to HDMI converter cable Vehicle dock ix Office dock Pen holder

Bumper-to-Bumper warranty Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime. That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

	Getac-made Vehicle Dock (JAE)	Havis Vehicle Dock (Pogo,power only)	Havis Vehicle Dock (JAE)	Gamber-Johnson Charging Cradle (Pogo)	Havis Vehicle Dock (Pogo)	Office Dock (JAE)	Office Dock (Pogo)
Serial Port	1	-	1	-	1	-	-
Speaker	1	-	-	-	-	-	-
Audio Output	1	1	1	-	1	1	1
DC in Jack	1	1	1	1	1	1	1
USB	USB Host x 2	-	USB2.0 x 2	-	USB2.0 x 2	USB Host x 2 MicroUSB Client x 1	USB Host x 2
LAN	1	-	1	-	1	1	1
HDMI	1	-	1	-	-	1	-
RF Antenna Connector	(WWAN, GPS)	(WWAN, GPS)	(WWAN, GPS)	-	(WWAN, GPS)	-	-

ZX70 FULLY **RUGGED TABLET**

- Android enterprise recommended rugged devices deliver a consistent set of features verified by Google with an elevated device baseline, increased security standards and enterprise-focused features and behaviors to meet the needs of users. Google and Android are trademarks of Google LLC.
 Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
 Units with 4G LTE option comes with an embedded SIM card slot.
 H 3.56MHz HF RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
 HF RFID/NFC combo reader applies to US & EU.
 Weight and dimensions vary from configurations and optional accessories.
 Drote st results vary from configurations and optional accessories. Ш
- IV.
- VI.
- VII.
- optional accessories. Tested by an independent third-party test lab following MIL-STD-810H. Havis vehicle dock is e-mark certified. VIII.

Information provided herewith is for reference only, available specification shall be subjected to quotation by reauest.

Getac



GETAC TECHNOLOGY CORPORATION

5F, Building A, No. 209, Section 1, Nangang Rd., Nangang Dist., Taipei City, 115018, Taiwan, R.O.C. Tel : +886 2 2785 7888 globalmarketing@getac.com I www.getac.com Copyright © 2022 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only available specification shall be subjected to quotation by request.