




| | | | | |
|-----|------|------|-------------|----------|
| | | | | |
| | | | | |
| REV | CHG. | DATE | DESCRIPTION | REVISION |



Protecting Cap
M12x4

SOURCE DRAWING-FOR REFERENCE ONLY

| | | | | | | | | | | | | | |
|--------------------------------------|--|--------------|--|---|--|--|--|----------------|--|--------------|--|-------|--|
| APPROVED BY | | DATE | | <div>UNITRONICS®</div> | | | | | | | | | |
| CHECKED BY | | DATE | | | | | | | | | | | |
| DRAWING BY | | DATE | | | | | | | | | | | |
| ALEX | | 2023.8.9 | | | | | | | | | | | |
| TOLERANCE UNLESS OTHERWISE SPECIFIED | | CABLE LENGTH | | TOLERANCE | | UNITS | | mm | | DESCRIPTION: | | | |
| | | ALL LENGTHS | | +4%(OR 50mm) OF LENGTH -0%(OR 0mm) OF LENGTH WHICHEVER IS GREATER | | <div>1st Angle Projection</div> <div></div> | | ULK-1616P-M2P6 | | PART NO. | | | |
| | | STRIP LENGTH | | TOLERANCE | | | | REV | | A | | SHEET | |
| | | 0-7mm | | ±1.0mm | | | | | | | | | |
| | | 8-29mm | | ±1.5mm | | | | | | | | | |
| | | 30-49mm | | ±2.0mm | | | | | | | | | |
| | | 50-69mm | | ±3.0mm | | | | | | | | | |
| | | 70-100mm | | ±4.0mm | | | | | | | | | |
| | | over 100mm | | ±5.0mm | | | | | | | | | |