Getac

T800-Ex
FULLY RUGGED TABLET

- 8.1" HD LumiBond® 2.0 display for better viewing experience

- MIL-STD-810H and IP65 certified

- Enhanced Enterprise Security with TPM2.0, Windows Disk Encryption

CERTIFIED MIL-STD 810H | **INGRESS PROTECTION IP65** | **6' Drop** | **ATEX Ex** | **IEC.** | **IECEx**

SnapBack add-on

(Optional) 1D / 2D Imager Barcoder Reader
8MP Camera
FHD Webcam

Volume Up
Volume Down
Windows Key
Power Button
Function Key 1
Function Key 2

DC in
USB 3.0
Micro HDMI
Audio In / Out Combo

Rugged Mobile Computing Solutions

Specifications

Operating System
Windows 10 Pro

Mobile Computing Platform
Intel® Atom Processor x7-Z8750 1.6GHz, burst up to 2.56GHz
- 2MB Cache

VGA Controller
Intel® HD Graphics

Display
8.1" IPS TFT LCD HD (1280 x 800)
600 nits LumiBond® display with Getac sunlight readable technology

Storage & Memory
4GB LPDDR3
Optional: 8GB LPDDR3
128GB eMMC
Optional: 256GB eMMC

Keyboard
Power button
5 tablet programmable buttons

Pointing Device
Touchscreen
  - Capacitive multi-touch screen
  - Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot
Optional: 1D / 2D imager barcode reader x1

I/O Interface
FHD webcam x 1
8M pixels auto focus rear camera x 1
Headphone out/Mic-in Combo x 1
DC in Jack x 1
USB 3.0 x 1
Micro HDMI x 1

Communication Interface
Intel® Dual Band Wireless-AC 7265, 802.11ac
Bluetooth (v4.2)
Optional: Dedicated GPS
Optional: 4G LTE mobile broadband

Security Feature
TPM 2.0

Power
AC adapter (65W, 100-240VAC, 50 / 60Hz)
Li-Ion battery (7.4V, typical 4200mAh; min. 4080mAh)[i]

Dimension (W x D x H) & Weight
227 x 151 x 24 mm (8.93" x 5.94" x 0.94")
0.91 kg (2 lbs)[i]

Rugged Feature
MIL-STD-810H certified and IP65 certified
Vibration & 6 feet drop resistant

Environmental Specification
Temperature[ii]:
  - Operating: -21°C to 50°C / -6°F to 122°F
  - Storage: -51°C to 71°C / -60°F to 160°F
Humidity:
  - 95% RH , non-condensing

Explosion Protection
ATEX / IECEx zone 2 / 22
Ex II 3G Ex ic IIC T4 Gc
Ex II 3D Ex ic IIIB T130°C Dc

Software
Getac Utility
Getac Barcode Manager
Getac Camera
Optional: Absolute Persistence®

Accessories
Battery (7.4V, typical 4200mAh; min. 4080mAh)
2nd Expanded Battery (14.4V, 2100 mAh)
AC Adapter (65W, 100-240VAC)
Digitizer Pen
Capacitive Stylus (Hard-tip)

Bumper-to-Bumper warranty
Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee.

That means you can depend on us to have your unit back in service within days.

Standard
3 years Bumper-to-Bumper

---

i   Weight and dimensions vary from configurations and optional accessories.
ii Tested by a national independent third party test lab following MIL-STD-810H.

![Getac logo]