Getac

Rugged Mobile Computing Solutions

ZX70

Fully Rugged Tablet

- 7'' LumiBond® Display Sunlight Readable Technology and Glove-enabled Capacitive Touchscreen
- 6 Feet Drop , MIL-STD-810G and IP67 Certified
- Optional Barcode Reader and RFID Reader
- Optional 4G LTE WWAN
- High Sensitivity GPS

CERTIFIED MIL-STD 810G | INGRESS PROTECTION IP67 | 6' Drop | ATEX



Office Dock

Vehicle Dock



Rugged Mobile Computing Solutions

ZX70 Fully Rugged Tablet

Specifications

Operating System	Android 6.0
Mobile Computing Platform	Intel Atom® Processor x5-Z8350 1.44GHz, burst up to 1.92 GHz - 2MB cache
VGA Controller	Intel® HD Graphics
Display	7" IPS TFT LCD HD (1280 x 720) LumiBond® display with Getac sunlight readable technology Capacitive touchscreen with glove on
Storage & Memory	2GB LPDDR3 expandable to 4GB eMMC 32GB / 64GB
Keyboard	4 tablet buttons (Power, Barcode Launch Button, Volume Up, Volume Down)
Pointing Device	Touchscreen - Capacitive multi-touch screen
Expansion Slot	MicroSD x1
I/O Interface	FHD webcam x 1 8M pixels auto focus rear camera x 1 MicroUSB 2.0 (Client) x 1 USB 2.0 (Host) x 1 Docking connector (Pogo/JAE) DC in Jack x 1 MicroSD x 1 Optional RF antenna pass-through for GPS and WWAN
Communication Interface	Wi-Fi 802.11 n Bluetooth (v4.0)[i] Dedicated GPS Optional 4G LTE mobile broadband
Software	Getac Settings, Google Chrome, Gmail, Google+, Google Maps, Google Play Music, Google Play Movies, Google Play Books, Google Play Newsstand, Google Play Games, Google Drive, YouTube, Google Plus Photos, Hangouts
Security Feature	Optional Contactless RFID/NFC combo reader[ii, iii] Optional Barcode reader Optional UHF RFID reader[iv, v]
Power	AC adapter (24W, 100-240VAC, 50 / 60Hz) Li-Ion battery (3.8V, 8400mAh)
Dimension (W x D x H) & Weight	218 x 142 x 27 mm (8.58 " x 5.6" x 1.08") 780g (1.71lbs)[vi]
Rugged Feature	MIL-STD-810G certified and IP67 certified 6 feet drop resistant Vibration & drop resistant e-Mark certified for vehicle usage
Environmental Specification	Temperature[vii]: - Operating: -21°C to 60°C / -6°F to 140°F - Storage: -40°C to 71°C / -40°F to 160°F Humidity: - 95% RH , non-condensing
Accessories	Carry bag AC adapter (24W; 12V/2A, 100-240VAC; 50 / 60 Hz) Vehicle adapter (60W, 11-16VDC and 22-32VDC) Capacitive stylus Rotating Hand strap with Kick Stand and Stylus Holder Office dock Vehicle dock USB to RS232 converter cable Docking connector to HDMI converter cable Protection film Shoulder strap Wrist strap

Docking solutions

	USB Host	*USB Client*	*HDMI*	*Audio Output*	*Speaker*	*LAN*	*RS232*	*DC in Jack*	*RF Pass through*
Getac Office dock (JAE connector)	2	1	1	1	N/A	1	N/A	1	N/A
Getac Office dock (Pogo pin)	2	N/A	N/A	1	N/A	1	N/A	1	N/A
Getac Vehicle dock (JAE connector)	2	N/A	1	1	1	1	1	1	2 (WWAN, GPS)
Getac Vehicle dock (Pogo pin)	2	N/A	N/A	1	1	1	1	1	2 (WWAN, GPS)

i Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
ii 13.56MHz Contactless RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
iii RFID/NFC combo reader applies to US & EU only.
iv UHF RFID reader is mutually excusive with Barcode reader.
v EU only (865~868MHz, UHF RFID tags of EPC Class 1 Gen2 ISO18000-6C standards compliant).
vi Weight and dimensions vary from configurations and optional accessories.
vii Tested by a national independent third party test lab following MIL-STD-810G.

Getac

Getac Technology Corporation

5F, Building A, No. 209, Section 1, Nangang Rd., Nangang Dist.,
Taipei City, 11568, Taiwan, R.O.C.
Tel: +886 2 2785 7888
globalmarketing@getac.com
www.getac.com

Copyright © 2017 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
Information provided herewith is for reference only,
available specification shall be subjected to quotation by request. V02M06Y17WW

RUGGEDCOMPL
RUGGED INDUSTRIAL SOLUTIONS

Elmark Automatyka
rugged@elmark.com.pl
+48 22 773 79 37
www.rugged.com.pl